





Apollo[®] Valve Backflow Preventers Model Codes



Apollo[®] Valve Backflow Preventers Factory Codes



	MODEL CODES	FACTORY CODES
Backflow Device	Series	
Double Check Valve Assemblies (DC)	DC 4A (LF)	4A 10X (4ALF)
	DCLF 4An	4AnLF 10X
	DC 4SG, 4SGLF	4SG 10X, 4SGLF 10X
Double Check Detector Assemblies (DCDA)	DCDA LF 4A	4ALF 62X
	DCDA 4AnLF	4AnLF 62X
	DCDA 4SG, 4SGLF	4SG 60X, 4SGLF 60X
Reduced Pressure Assemblies (RP)	RP 4A (LF)	4A 20X (4ALF)
	RP 4AnLF	4AnLF 20X
Reduced Pressure Detector Assemblies (RPDA)	RPDA 4ALF	4ALF 72X
	RPDA 4AnLF	4AnLF 72X
Options		
Std. "81" metal Bronze	No Code	No Code
Lead Free Bronze	LF	LF
No Strainer (Standard 1/2" - 12")	No Code	No Code
With Wye Strainer	YS	1
Type - Detector Bypass Configuration Orientation determined by facing downstream		
Type 2 - Standard & on Right Side (except 4SG on top)	2	2
Type 1 - On Right Side (Except 4SG - on top)	1	No Code
Type 3 (Same as Type 1, Only on Left Side)	3	3
Type 4 (Same as Type 2, Only on Left Side)	4	4
Size		
1/4'	14	1
3/8"	38	2
1/2"	12	3
3/4"	34	4
1"	1	5
1 1/4"	114	6
1 1/2"	112	7
2"	2	8
2 1/2"	212	9
3"	3	0
4"	4	A
6"	6	C
8"	8	E
10"	10	G
12"	12IN	H
Detector Assembly Meters		
Cubic feet Meter	CFM	C
Gallons Meter	GPM	E
Less Meter	LM	G



	MODEL CODES	FACTORY CODES
Assembly Shutoff Valve Options		
1/2" - 2"		
Less Shutoffs	LS	T1
Ball Valves FNPT	Standard No Code	A2
Union Ball Valves	UBV	A4
Press Connection	PR	PR
Push Connection	P	P
2 1/2" - 12"		
Less Shutoffs	LS	1
NRS FXF	NF	2
NRS FXG	NFG	12
NRS GXG	NG	11
OSY FXF	OF	3
OSY FXG	OFG	7
OSY GXG	OG	8
F OSY X Butterfly G	OFBG	4
F OSY X Post Indicator F	OFPIF	6
F OSY X Post Indicator G	OFPIG	5
G Butterfly X Butterfly G	BG	9
G Butterfly X Post Indicator F	BGPIF	15
F Ball Valve X Ball Valve F	FBV	5
F Post Indicator X Butterfly G	PIFBG	13
F Post Indicator X Post Indicator F	PIFPIF	14
F Post Indicator X OSY G	PIFOG	17
G OS&Y x Post Indicator G	OGPIG	18
G Butterfly x Post Indicator G	BVGPIG	19
F Post Indicator x OS&Y F	PIFOF	20
G Post Indicator x OS&Y G	PIGOF	21
G Post Indicator x Butterfly G	PIGBG	22
G Butterfly x OS&Y F	GBOF	23
Testcock Options		
1/8" SAE Flare (Standard 1/2" - 1" Assemblies)	F	F
1/4" FNPT (Standard 1 1/4" - 2" Assemblies)	No Code	No Code
1/2" FNPT (Standard 2 1/2" - 4" Assemblies)	No Code	No Code
3/4" FNPT (Standard 6" - 12" Assemblies)	No Code	No Code
Shutoff Valve Handle Options		
"T" Handles (Standard on 1/2" - 1" Assemblies)	No Code	No Code
Level Handles (Standard on 1 1/4" - 2" Assemblies)	No Code	No Code
Locking Lever Handles (1/2" - 2")	LL	LL
Dual Check, DCAP Options - Inlet, Outlet Options		
FNPT	F	A
MNPT	M	B
Solder	S	H
F Meter Threads	FMR	C
M Meter Threads	MMR	E
F Swivel Meter Threads	FSMTR	S
F BSPP	FBSP	F
Chrome Plating Options (Selected Models)		
Rough Chrome	RC	03
Satin Chrome	SC	CS
Polished Chrome	PC	06